



## ➤ PRODUCT BULLETIN

# ColorMatrix™ Liquid Dispersion for Extrusion Blow Molding

Avient's ColorMatrix™ LCX liquid color products are the latest advancement in technology to deliver stable pigment dispersions for the extrusion blow molding (EBM) process.

These highly concentrated liquid formulations deliver a consistent finish with repeatable and dependable processing. They may also provide significant Let Down Ratio (LDR) reduction versus traditional masterbatch options. ColorMatrix LCX dispersions are designed to minimize and eliminate screw slip, streaking and specking, all while generating cost-to-color savings through processing efficiencies that include:

- **Handling efficiency** – bulk distribution, individual feed stations
- **Inventory reduction** – less inventory and required floor space
- **Process efficiency** – improved color change times

## KEY CHARACTERISTICS

- Highly concentrated pigment dispersions specifically for EBM processing
- Provides dimensional stability by utilizing more resin instead of fillers
- Reduces costs through handling and processing efficiencies
- Customization available for design and product handling
- Can be formulated in combination with a wide selection of additive technologies to meet performance needs

## MARKETS AND APPLICATIONS

ColorMatrix LCX Liquid Dispersions for EBM processing are well suited for the following:

- Monolayer applications
- LDR less than 3%
- Large volume whites and blacks
- Tints

1.844.4AVIENT  
[www.avient.com](http://www.avient.com)



Copyright © 2021, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.